

Safety data sheet
 according to UK REACH

Page 1/13

Printing date 04.07.2025

Revision: 04.07.2025

Version number 9.04 (replaces version 9.03)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** butan-1-ol

· **Article number:** 1082

· **CAS Number:**

71-36-3

· **EC number:**

200-751-6

· **Index number:**

603-004-00-6

· **Application of the substance / the mixture** Laboratory chemicals

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

PANREAC QUIMICA S.L.U.

C/Garraf 2

Polígono Pla de la Bruguera

E-08211 Castellar del Vallès (Barcelona)

Tel. (+34) 937 489 400

Fax. (+34) 937 489 401

e-mail: product.safety@itwreagents.com

· **Further information obtainable from:** email: product.safety@panreac.com

· **1.4 Emergency telephone number:**

Single telephone number for emergency calls: 112 (EU)

Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Trade name: butan-1-ol

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS07

· **Signal word** Danger

· **Hazard statements**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.1 Substances**

· **CAS No. Description**

71-36-3 butan-1-ol

· **Identification number(s)**

· **EC number:** 200-751-6

· **Index number:** 603-004-00-6

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Involve doctor immediately.

· **After inhalation:**

Supply fresh air.

If breathing stops: mouth-to-mouth respiration or mechanical ventilation, oxygen mask if necessary.

Immediately call a physician.

(Contd. on page 3)

Trade name: butan-1-ol

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

· **After skin contact:**

Call a doctor immediately.

Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Risk of aspiration!

Call a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* **SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Combustible.

Forms explosive mixtures with air at ambient temperatures.

Vapours are heavier than air and may spread along floors.

Beware of backfiring.

Forms explosive mixtures with air on intense heating.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

· **Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Contain escaping vapours with water.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Avoid substance contact.

Do not inhale steams/aerosols.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Clean up affected area.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Trade name: butan-1-ol

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Keep receptacles tightly sealed.
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.
- Protect from heat.
- Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

- Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility:** Away from sources of ignition and heat.
- Further information about storage conditions:**
 - Keep container tightly sealed.
 - Protect from heat and direct sunlight.
 - Open receptacle only under localised extractor facilities.
 - Store receptacle in a well ventilated area.
 - Store under lock and key and with access restricted to technical experts or their assistants only.

Recommended storage temperature: Room Temperature

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm
Sk	

DNELs

Inhalative	Long-term - systemic effects, worker	310 mg/m ³
	Long-term - local effects, worker	310 mg/m ³
	Long-term - systemic effects, general population	55 mg/m ³
	Long-term - local effects, general population	55 mg/m ³

PNECs

Aquatic compartment - freshwater	0.082 mg/L
Aquatic compartment - marine water	0.0082 mg/L
Aquatic compartment - water, intermittent releases	2.25 mg/L
Aquatic compartment - sediment in freshwater	0.178 mg/kg
Aquatic compartment - sediment in marine water	0.0178 mg/kg
Terrestrial compartment - soil	0.015 mg/kg

Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

Trade name: butan-1-ol

(Contd. of page 4)

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Filter A-(P2)
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
- **As protection from splashes gloves made of the following materials are suitable:**
Chloroprene rubber, CR
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
- **Eye/face protection**



Gauze goggles

- **Body protection:**
Use protective suit.
Flame retardant antistatic protective clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** Colourless
- **Odour:** Alcohol-like
- **Odour threshold:** Not determined.

(Contd. on page 6)

Trade name: butan-1-ol

(Contd. of page 5)

· Melting point/freezing point:	-89 °C
· Boiling point or initial boiling point and boiling range	117-118 °C
· Flammability	Not applicable. Flammable.
· Lower and upper explosion limit	
· Lower:	1.4 Vol %
· Upper:	11.3 Vol %
· Flash point:	35 °C
· Auto-ignition temperature:	340 °C
· Decomposition temperature:	Not determined.
· pH	7
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	2.95 mPas
· Solubility	
· water at 20 °C:	75 g/l
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	6.7 hPa
· Density and/or relative density	
· Density at 20 °C:	0.81 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.

· **9.2 Other information**

· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	100 %
· Molecular weight	74.12 g/mol
· Change in condition	
· Evaporation rate	Not determined.

· **Information with regard to physical hazard classes**

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void

(Contd. on page 7)

Trade name: butan-1-ol

(Contd. of page 6)

- | | |
|----------------------------------|------|
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Warming. A range from approx. 15 Kelvin below the flash point is to be rated as critical.
- **10.3 Possibility of hazardous reactions**
Increased reactivity with:
alkali metals
acid chlorides
aluminium
strong reducing agents
- **10.4 Conditions to avoid** Keep away from open flames, hot surfaces and sources of ignition.
- **10.5 Incompatible materials:**
sulfuric acid
Nitric acid
- **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5
- **Additional information:**
rubber
varous plastics

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if swallowed.
- **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
Oral	LD50	2,292 mg/kg (rat)	
Dermal	LD50	3,430 mg/kg (rabbit)	

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **After inhalation:** Irritant to skin and mucous membranes.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties** Substance is not listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

Type of test	Effective concentration	Method	Assessment
EC50/48 h	1,328 mg/l (daphnia magna)		

(Contd. on page 8)

Trade name: butan-1-ol

(Contd. of page 7)

EC50/96 h 129 mg/l (Algae)

225 mg/l (algae)

LC50/96 h 1,376 mg/l (fish)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Chemicals must be disposed of in compliance with the respective national regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1120

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA**

BUTANOLS

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

(Contd. on page 9)

GB

Trade name: butan-1-ol

(Contd. of page 8)

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**
· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Flammable liquids.
· **Hazard identification number (Kemler code):** 30
· **EMS Number:** F-E,S-D
· **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
· **Transport category** 3
· **Tunnel restriction code** D/E

· **IMDG**
· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1120 BUTANOLS, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**
- **Regulated explosives precursors** Substance is not listed.
- **Regulated poisons** Substance is not listed.
- **Reportable explosives precursors** Substance is not listed.
- **Reportable poisons** Substance is not listed.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Substance is not listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

GB

(Contd. on page 10)

Trade name: butan-1-ol

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

Annex: Exposure scenario 1

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
Filter A-(P2)
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 11)

Trade name: butan-1-ol

(Contd. of page 10)

Use suitable respiratory protective device only when aerosol or mist is formed.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 2

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity** ≤ 1 tons per day
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
Filter A-(P2)
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.

(Contd. on page 12)

Trade name: butan-1-ol

(Contd. of page 11)

- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures**
Disposal must be made according to official regulations.
Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Worker (dermal)** The calculated value is smaller than the DNEL.
- **Worker (inhalation)** The calculated value is smaller than the DNEL.
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 3

- **Short title of the exposure scenario** Use in laboratories
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Used amount per time or activity** Smaller than 100 g per application.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
Indoor application.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
Filter A-(P2)
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.

(Contd. on page 13)

Trade name: butan-1-ol

(Contd. of page 12)

- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures**
Disposal must be made according to official regulations.
Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Worker (dermal)** The calculated value is smaller than the DNEL.
- **Worker (inhalation)** The calculated value is smaller than the DNEL.
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB