

Safety data sheet
 according to 1907/2006/EC, Article 31

Page 1/9

Printing date 06.06.2023

Revision: 27.05.2023

Version number 1.01 (replaces version 1.00)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Mounting Medium for substitutes of xylene
- **Article number:** 5811
- **Application of the substance / the mixture** Laboratory chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 PANREAC QUIMICA S.L.U.
 C/Garraf 2
 Polígono Pla de la Bruguera
 E-08211 Castellar del Vallès (Barcelona)
 Tel. (+34) 937 489 400
 Fax. (+34) 937 489 401
 e-mail: product.safety@itwreagents.com
- **Further information obtainable from:** email: product.safety@panreac.com
- **1.4 Emergency telephone number:**
 Single telephone number for emergency calls: 112 (EU)
 Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
 Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 C11-15-Isoalkanes

(Contd. on page 2)

GB

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 1)

isobutyl methacrylate

· **Hazard statements**

H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P331 Do NOT induce vomiting.
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 90622-58-5 EC number: 918-167-1 Reg.nr.: 01-2119472146-39-XXXX	C11-15-Isoalkanes Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413, EUH066	>50-<100%
CAS: 97-86-9 EINECS: 202-613-0	isobutyl methacrylate Flam. Liq. 3, H226; Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335	>1-≤2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:** Involve doctor immediately.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Call a doctor immediately.
Immediately wash with water and soap and rinse thoroughly.
Immediately remove any clothing soiled by the product.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Call a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
In order to avoid contact with skin, keep a safety distance and wear suitable protective clothing.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Contain escaping vapours with water.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid substance contact.
Do not inhale steams/aerosols.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Clean up affected area.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Open receptacle only under localised extractor facilities.
Store under lock and key and with access restricted to technical experts or their assistants only.
Keep container sealed.
- **Recommended storage temperature:** Room Temperature

(Contd. on page 4)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 3)

- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
- **As protection from splashes gloves made of the following materials are suitable:**
Recommended thickness of the material: ≥ 0.11 mm
Value for the permeation: Level ≥ 480 min
- **Eye/face protection** Safety glasses
- **Body protection:**
Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled.

GB
(Contd. on page 5)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	180-270 °C (Hydrocarbons, C11-C14, n-Alkanes, Isoalkanes, Cyclenes, <2 % Aromatics)
· Lower and upper explosion limit	
· Lower:	0.6 Vol % (Hydrocarbons, C11-C14, n-Alkanes, Isoalkanes, Cyclenes, <2 % Aromatics)
· Upper:	7 Vol % (Hydrocarbons, C11-C14, n-Alkanes, Isoalkanes, Cyclenes, <2 % Aromatics)
· Flash point:	>70 °C (Hydrocarbons, C11-C14, n-Alkanes, Isoalkanes, Cyclenes, <2 % Aromatics)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	0.3 hPa (Hydrocarbons, C11-C14, n-Alkanes, Isoalkanes, Cyclenes, <2 % Aromatics)
· Density and/or relative density	
· Density at 20 °C:	0.803 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void

(Contd. on page 6)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 5)

- | | |
|--|------|
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
90622-58-5 C11-15-Isoalkanes			
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (mouse)	

- **Serious eye damage/irritation**
- **After inhalation:** No irritant effect.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 6)

- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Chemicals must be disposed of in compliance with the respective national regulations.
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN number or ID number
· ADR, IMDG, IATA | Void |
| · 14.2 UN proper shipping name
· ADR, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es)
· ADR, ADN, IMDG, IATA
· Class | Void |
| · 14.4 Packing group
· ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 8)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H413 May cause long lasting harmful effects to aquatic life.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Dept. Compliance

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1B: Skin sensitisation – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

· *** Data compared to the previous version altered.**

Annex: Exposure scenario

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** Use only on hard ground.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin.
Avoid long-term or repeated skin contact.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.

(Contd. on page 9)

Trade name: Mounting Medium for substitutes of xylene

(Contd. of page 8)

- **Technical protective measures**
Use product only in enclosed systems.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water** Do not allow to reach sewage system.
- **Soil** Prevent contamination of soil.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB